



JX Peterbilt-Waukesha P123
 820 Silvernail Road, Suite A

SUPER PRODUCTS
 17000 W. Cleveland Ave.

Pewaukee, Wisconsin United States 53072
Phone: (847) 340-5471
Fax:
Email:

New Berlin, Wisconsin United States 53151
Phone: (262) 784-7100
Fax:
Contact Email:
Prepared for:

Vehicle Summary

	Unit		Chassis	
Model:		Model 365	Fr Axle Load (lbs):	20000
Type:		Full Truck	Rr Axle Load (lbs)	40000
Description:		CAMEL 1200EJ 2021MY	G.C.W. (lbs):	60000
	Application		Road Conditions:	
Intended Serv.:		Tanker, Liquid Bulk	Class A (Highway)	90
Commodity:		Other Commodity	Class B (Hwy/Mtn)	10
	Body		Class C (Off-Hwy)	0
Type:		Vacuum	Class D (Off-Road)	0
Length (ft):		20	Maximum Grade:	6
Height (ft):		13.5	Wheelbase (in):	257
Max Laden Weight (lbs):		1000	Overhang (in):	52
	Trailer		Fr Axle to BOC (in):	68.9
No. of Trailer Axles:		0	Cab to Axle (in):	188.1
Type:			Cab to EOF (in):	240.1
Length (ft):		0	Overall Comb. Length (in):	387
Height (ft):		0.0		
Kingpin Inset (in):		0	Special Req.	
Corner Radius (in):		0	United States Registry	
	Restrictions			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		

Approved by: _____ **Date:** _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
 Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



JX Peterbilt-Waukesha P123
820 Silvernail Road, Suite A

SUPER PRODUCTS
17000 W. Cleveland Ave.

Pewaukee, Wisconsin United States 53072
Phone: (847) 340-5471
Fax:
Email:

New Berlin, Wisconsin United States 53151
Phone: (262) 784-7100
Fax:
Contact Email:
Prepared for:

Data	Code	Description	\$ List	Weight
Base Model				
0003651	O	Model 365 Peterbilt's powerful and versatile Model 365 is built to meet the daily challenges of mixer duty, construction sites and virtually any vocational application. The lightweight, all-aluminum cab with lap seam construction, aircraft grade fasteners and bulkhead style doors is legendary for its durability. With a compact 115-inch BBC, the 365 features improved ride and handling and increased maneuverability. The Model 365 is available in both a set-forward front axle configuration for a smoother ride or a set-back front axle for increased maneuverability and optimized weight distribution.	170,838	14,940
0091200	O	Other Commodity	0	0
0093020	O	Tanker, Liquid Bulk General freight (linehaul) service using a liquid bulk tanker body or tanker trailer.	0	0
0095130	O	Vacuum	0	0
0098170	O	United States Registry	0	0
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514020	O	10-3/4in Steel Rails 355-384in 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	482	575
0601500	O	Full Steel Inner Liner	1,411	799
0611250	O	Heavy-Duty Iron Front Spring Brackets Forward and Rear	298	35
0620190	O	FEPTO Prov,31in Reinforced Front Frame Extension Includes Stationary Grille and Engine Adapter for 1350 Flange Yoke.	2,372	119
0634170	O	Raised Steel X-Tie	151	20
0644090	O	EOF Square without Xmbr For use with body builder installed crossmember.	-31	-64
0651090	O	Omit Rear Mudflaps and Hangers	-57	-25

Front Axle & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
1011360	O	Dana Spicer D2000F 20,000 lb, 3.5 in. Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	1,715	111
1114030	O	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	536	132
1233060	O	Power Steering TRW TAS65 Dual For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	1,004	58
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler	210	2
1354840	O	PHP10 Iron PreSet PLUS Hubs	-827	-113
1380070	O	Greasable Front Spring Pins	49	0
1380270	O	Bendix Air Cam Front Drum Brakes 16.5x6 Includes automatic slack adjusters & outboard mounted brake drums.	416	-25
1391410	O	Gusseted Cam Brackets, Steer Axle	27	0
Rear Axle & Equipment				
1523300	O	Dana Spicer DSP41 40,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	573	142
1616290	S	PHP10 Aluminum PreSet PLUS Hubs	0	0
1631310	O	Standard Stroke Parking Brakes Drive Axle(s). Not for use on U.S. or Canada Tractors, other than Car Carriers.	-7	-20
1680030	O	Veeder Root Hubodometer, Miles	100	0
1680450	O	Rear Brake Camshaft Reinforcement	120	9
1680470	O	Lube Pump, Drive Axle(s) Used to circulate oil within the axle housing. Recommended for use on 46K or greater axles used in refuse or severe service applications.	432	36
1680490	O	Gusseted Cam Brackets, Drive Axle(s)	70	2

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
1680500	O	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	219	0
1680950	O	Stability System Not Selected or Not Available	-101	0
1682430	O	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	-434	-30
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1705290	O	Ratio 5.29 Rear Axle	0	0
1822160	O	Hendrickson RT403 40,000 lb, 52in Axle Spacing	2,763	580

Engine & Equipment

2074507	O	PACCAR PX-9 370@1900 GOV@2100 1250@1400 Performance (2017 Emissions) N21320 N205 68...Standard Maximum Speed Limit [LSL] N21330 N207 0...Expiration Distance N21350 P001 70...Maximum Accelerator Pedal Vehicle Speed N21370 P059 70...Maximum Cruise Speed N21400 N203 252...Reserve Speed Function Reset Distance N21410 N202 0...Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0...Reserve Speed Limit Offset N21440 P015 YES..Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 NO...Cruise Control Auto Resume N21480 P068 NO...Auto Engine Brake in Cruise N21500 N209 0...Expiration Distance N21510 P520 YES..Enable Idle Shutdown Park Brake Set N21520 P030 5...Timer Setting N21530 P233 YES..Enable Impending Shutdown Warning N21540 P234 60...Timer For Impending Shutdown Warning N21550 P516 35...Engine Load Threshold N21570 P031 NO...Idle Shutdown Manual Override N21590 P230 YES..Enable Hot Ambient Automatic Override N21610 P172 40...Low Ambient Temperature Threshold N21620 P173 60...Intermediate Ambient Temperature Threshold N21630 P171 80...High Ambient Temperature Threshold	-8,047	-1,070
2091310	O	Engine Idle Shutdown Timer Disabled	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372	O	Eff EIST NA Expiration Miles	0	0
2091640	O	Effective VSL Setting NA	0	0
2140150	O	Remote PTO And Throttle Provision	67	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2147460	O	Bed Plate for PX-9, L9N	48	0
2513060	S	PACCAR 160 Amp Alternator, Brushed	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522110	O	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	322	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539740	O	Kissling Battery Disconnect Switch, 300 amp Mounted on battery box	541	3
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops	322	0
2723210	O	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	-33	17
2921110	S	PACCAR Fuel/Water Separator Standard Service Interval	0	0
2921210	O	No Fluid Heat Option for Fuel Filter	0	0
2921320	O	12V Heat for Fuel Filter	66	0
3010400	O	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	6	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0	0
3291680	S	(1) Air Cleaner Firewall Mounted Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365270	S	Exhaust Single RH Side Of Cab DPF/SCR RH Under Cab (2017).	0	0
3381770	O	Curved Tip Standpipe(s)	51	1
3387870	S	24in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	0	0

Transmission & Equipment

4052110	O	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.03)	10,063	-80
4210640	O	1760 HD Driveline, 3 Midship Bearings	1,818	260
4252890	O	Allison FuelSense 2.0 Not Desired	0	0
4252950	O	Omit Allison Neutral At Stop	0	0
4256470	O	Allison MD/HD/RDS 4th Gear Lockup AJ Allison Vocation Package 150. Split Shaft PTO Pumper/Vacuum except Fire Truck Pumper.	298	0
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions	0	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison Transmissions.	769	0

Air & Trailer Equipment

4510320	S	Bendix AD-IS Air Dryer W/Heater And Coalescing Filter	0	0
---------	---	---	---	---

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
4520420	O	Pull Cords All Air Tanks	7	1
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4611850	O	Omit Standard Trailer Connection Package (Omits 12ft A&E lines, Hose Tenna, and Hand Valve)	-242	-28
4613300	O	Body Connection w/(1) Trucklite Junction Box LH EOF	183	8

Tires & Wheels

5032630	O	FF: GY 20ply 425/65R22.5 G296 MSA Diameter = 44.4 inches; SLR = 20.6 inches	849	148
5133390	O	RR: GY 16ply 11R22.5 G182 RSD GHG Diameter= 42.1 inches; SLR= 19.6 inches	1,092	88
5190008	O	Code-rear Tire Qty 08	0	0
5220090	O	FF: Alcoa 823627 22.5X12.25 Clean Buff Finish Aluminum	762	-10
5310600	O	RR: Accur Stl Armor 50291PK 22.5X8.25 Heavy Duty, Two Hand Holes	356	136
5390008	O	Code-rear Rim Qty 08	0	0

Fuel Tanks

5554100	O	26in Aluminum 70 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	344	18
5602070	O	Location LH U/C 70 Gallon	0	0
5650490	O	Fuel Cooler Required with single fuel tank.	183	15
5652830	O	Polish All Fuel / Hydraulic Tank Straps Does not apply to Rectangular Def Tank straps.	83	0
5652890	O	DEF Tank Mounted LH BOC Models 220 and 520 mounted LH cab fender	0	0
5652990	O	Standard DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	S	DEF Tank Small	0	0
5760010	O	RH Tank None Furnished	-492	-86

Battery Box & Bumper

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
6010780	O	Aluminum Space Saver Battery Box RH BOC Battery access from side	29	-20
6030150	O	Rubber Battery Pad In Bottom Of (1) Battery Box Mat in box that holds batteries only	12	4
6040550	S	Aftertreatment RH U/C ALUMINUM Non-Slip Cab Entry Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic.	0	0
6121060	O	Steel Bumper Swept Back Painted Black, With FEPTO (2) Tow pin holes and step plates on top of bumper	138	79

Cab & Equipment

6515560	O	Alum Cab 115in BBC Fiberglass Hood SBFA Fenders w/polished crown, spring tilt assist. Proprietary anti-blow-down locking mechanism that keeps hood open during servicing & prevents unintentional closing. Hood latch each side secures hood to cowl. Proprietary all-alum cab is light weight & durable for long service life. One-piece roof reduces potential for leaks. Two-piece windshield for cost effective windshield replacement. Lap seam construction & aircraft fasteners has greater clamp load than rivets. Bulkhead style doors provide virtually water-tight, rattle-free performance. Extruded alum door frames for strength & durability. Full length, heavy-duty piano-type stainless steel door hinges & pins provide durability. View window in RH door for safety. Electric windshield wipers & washers w/intermittent wiper function. Grab handles mtd on cab LH & RH for cab access. Convex mirror over RH door & below each rear view mirror for improved visibility & safety.	0	170
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	22	2
6700000	O	No Sleeper Selected	0	0
6800340	O	Rubber Fender Lips 4 inch Extra Wide	255	8
6911700	S	Peterbilt UltraRide Driver Seat	0	0
6921700	S	Peterbilt UltraRide Passenger Seat	0	0
6930500	O	Drivers Armrest - RH Only	40	2
6930590	O	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	40	2
6930800	O	Black Seat Color ipo Standard Color	0	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939520	S	High Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7001520	O	Adjustable Steering Column - Tilt/Telescope	448	11

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
7001620	S	Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7039050	S	ProBilt Interior - Arctic Gray Includes rugged charcoal instrument panels, gray dash with glare-resistant, charcoal soft-touch upper, dark gray hard trim, black bezels on gauges, cigar lighter and ashtray with power port, monochromatic dark gray durable doorpads with map pocket on driver's side, dark gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, driver and passenger dome/reading lights, footwell lighting, integrated "dead pedal", (5) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, cup holder and map bin in dash.	0	0
7210420	O	Dark Window Tint ipo STD Tint - Day Cab	22	0
7210430	O	Extended Rear Window ipo Std Window-Day Cab The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	70	18
7210540	S	Day Cab Rear Window	0	0
7230350	O	Two Piece Flat Windshield	12	0
7230680	O	Power Lift Windows - Both Doors For use with ProBilt or Prestige Interior	27	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7322130	O	Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	70	4
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	295	4
7511010	O	Stainless Steel Mirrors 7x16 with Heat Element Right Click on Option to see Picture in Product Portfolio.	38	2
7560850	S	(2) Convex 8 Inch SS Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	0	0
7565180	O	Polished Lower Mirror Bracket Covers	16	0
7610020	O	(1) Air Horn 15in Painted Mounted under cab.	-31	0
7725710	O	Standard Speaker Package For Cab (2) Speakers	141	4
7725715	O	ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	379	10

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilt's proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesn't require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available.. SmartLINQ is standard with MX-13 engines and available on the models 587,579,567,389,367 and 365.	0	0
7850210	O	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	109	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7851970	O	Unibilt Cab Air Suspension Includes dual air bag suspension, leveling valve, and tracking rod.	612	25
7900090	O	Triangle Reflector Kit Shipped Loose	18	13
7900270	O	Fire Extinguisher; Cab Mounted Hazmat approved UL listed/rated ABC.	59	8
7901130	O	Backup Alarm (107dB)	60	3
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall.	0	0
8071340	O	Bright Bezel Gauges	50	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with tripodometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0	0
8072820	O	(2) Additional Air Rockers w/Blank Labels Guards and indicator lights, plumbed to firewall. (occupies the space of two gauges)	132	0
8111140	O	Headlights Projector Module Pod Integral Turn Signals	247	0
8120980	S	(5) Marker Lights, Aero LED Light Emitting Diodes	0	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20



Data	Code	Description	\$ List	Weight
8133470	O	Switch & Wiring For F/O Beacon/Strobe 10 ft coiled wire BOC/BOS at rear sill	72	2
8133960	O	Daytime Running Lights Required on all Canadian vehicles	60	0
8140080	O	LED Stop/Turn/Tail/Backup Bracket mounted LH/RH EOF	81	-7
8140850	O	Moveable EOF Xmbr For Mounting Taillights Square EOF with or without EOF xmbr.	141	1
8153100	O	(1) F/O Load Light, Switch & 10ft Wire Coil Under / in cab / sleeper	40	2

Paint

8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85400 HOOD TOP L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85200 FRAME L0001EA BLACK N85700 BUMPER L0001EA BLACK N85300 FENDER L0006EY WHITE	0	0

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9400094	O	PACCAR PX-9 Standard Coverage 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9408982	O	Vehicle Layout Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this. N94000 Per Layout	1,350	0

Miscellaneous

9409000	O	Day Cab / ProBilt Interior (DB)	0	0
9409800	O	2017 EPA Emissions Engine Warranty Only	0	0
9409960	O	Presentation Created Using Featured Spec For Model	0	0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)	\$195,249
Freight Charge	\$2,425
Options Not Subject to Discount	\$1,350
Surcharges Not subject to Discount	\$0
Total Weight	17051

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	5/8/2019 1:06:47 PM	Complete	Model Number:	Model 365
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q15612047
Prepared by:	Administrator		Version Number:	38.20